

4 Channels 1080N All in One DVR + 4 Bullet TVI IMPX Cameras

TECHNICAL SPECIFICATIONS FOR THE CAMERA

Image Sensor	1/4" OV9732 CMOS/720P
Camera Resolution	1 Megapixel
Effective Pixels	1280(H) x 720(V)
Infrared LED	36 pcs
Lens Mount	3,6mm
Format	TVI
Field of View	60° Degrees
Minimum Illumination	0 LUX (IR on)
IR Cut Filter	Yes
Night Vision Distance	82ft / 25m
Shutter Speed	NTSC (1/60 sec-1/100,000 sec)
Operative Temperature	14° ~ 122°F/ - 10° ~ 50°C
Ingress Protection	IP66
Power Supply	DC 12V/320mA (IR on)



TECHNICAL SPECIFICATIONS FOR DVR

VIDEO	
Video Input	DVR: 4CH 1080P Hybrid: 2CH 1080P + 2CH IP 1080P NVR: 4CH IP 1080P / 8CH IP 1080P / 4CH IP 3MPX
Video Output	VGA, HDMI
Display Resolution	Up to 1080P (1920 x 1080)
Display Split	DVR: 1/4 Screen Hybrid: 1/4 Screen NVR: 1/4, 8/9 Screen
AUDIO	
Audio Input	4 Channel RCA
Audio Output	1 Channel RCA
RECORDING	
Record Quality	Up to 1080N DVR mode, up to 1080P NVR mode
Video Compression	H.264 (High Profile)
Record Mode	Manual / Schedule / Motion / Alarms
PLAYBACK	
Simultaneously Playback	1/2/4 Channels
Backup Mode	USB Device, Web Browser, Mobile App
Playback Quality	Up to 1080P (1920 x 1080)
STORAGE	
HDD Port	2 SATA Port
HDD Capacity	Up to 4TB
EXTERNAL PORTS	
USB Port	2 Ports, USB 2.0
RS485	1 Port for PTZ Control
Ethernet	1 RJ-45 Port (10/100Mbps)
GENERAL	
Power Supply	DC 12V/3A
Video System	NTSC/PAL Switch Selectable
Remote Access	Cloud System For Remote Access, NO Port Mapping
Compatibility For	iOS, Android
Compatible Video Format	AHD/TVI/CVI/CBVS

MODEL: LX441BN



LOGAN LIVE FREE APP

