


4MPX Dome PoE IP Camera

TECHNICAL SPECIFICATIONS FOR THE CAMERA	
CAMERA	
Image Sensor	1/3" Progressive CMOS
Camera Resolution	4 Megapixel
Effective Pixels	2592(H) x 1520(V)
Infrared LED	40pcs(SMD)
Lens Mount	2.8 - 12 mm (Motorized varifocal) 4x Optical Zoom, 3x Digital Zoom
IMAGE SETTINGS & FEATURES	
Shutter Speed	1/5 - 1/20000s
Backlight	Enable/Disable
Day & Night	IR cut filter with auto switch/ IR cut delay
Wide Dynamics Range	90dB
Night Vision Distance	30 to 100 feet (surface-mount IR LED)
Minimum Illumination	Color 0.1lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Digital Noise Reduction	3D Disable/ Auto/ Manual
Defog Mode	Disable/ Auto/ Manual
Privacy Zone	Up to 4 zones
Roi (Region Of Interest)	Up to 8 regions, ROI level can be adjusted
VIDEO	
Compression Standard	H.265/H.264
Field of View	29°-91° Degrees
Frame Rate	Mainstream 4MP(2539X1520)/ 3MP(2048X1520)/ Super HD(2304X1296)/Full HD 2MP(1920X1080)/ 1280X960/ HD 1MP(1280X720) (25/30fps) Substream D1(704X480)/ VGA(640X480)/ QVGA(320X240) (25/30fps) Mobile stream QVGA(320X240) (25/30fps)
Image settings	Rotate mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or via web browser
Recording Mode	Continuous/ Smart Scheduled / Motion Detection/ Alarm Out/Pre-recording can be setup for main & substream Record to a compatible NVR/NAS device/ Local PC
NETWORK & ADVANCED	
Interface	RJ45 10M / 100M
System Compatibility	ONVIF (Ver 2.6)
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Security & Videos Analytics	Triple transmission/ Password protection/ Privacy mask/ IP address filtering/ Motion detection alerts and alerts, camera view manipulation/ Intelligent video analysis (perimeter intrusion, cross line, stationary object) Daily reports/ Weekly/ Monthly/ Yearly (lists, histogram, graph)
Mobile views	Supported (compatible for iOS, Android)
Video management software	Compatible with Windows PC, Apple Mac
GENERAL	
PoE	Yes
Ingress Protection	IP66
Operative Temperature	-30 - +55°C
Power Supply	DC 12V/POE (7W)



MODEL: LP4WACS



ULTRA HD
2K

